

SP MINI KIT

The ultra-compact, handy device for targeted or occasional steam bio-cleaning.



■ ■ Manufactured in France by Sanivap according to ISO 13485.

The **SP MINI Kit** ensures bio-cleaning of surfaces: floors, ceilings, walls, furniture, medical devices, etc.

The constant quality of the steam from the **SP MINI Kit** stops surfaces from becoming dirtied again and ensures optimal cleaning and disinfecting: bactericidal, yeasticidal, fungicidal, virucidal. Compatible with a wide range of suitable accessories. Ergonomic, easy to handle and ideal for professional maintenance protocols that require rapid use.



EASE OF USE

Device fitted with a thumbwheel control keyboard and settings for the different ranges to simplify its use.



ECONOMY

Water consumption and time are reduced without the use of chemicals.



ENVIRONMENTALLY FRIENDLY

100% immediately biodegradable and no pollutant discharge.



RELIABILITY AND PERFORMANCE

Intensive professional use, autonomy up to 8 hours per day and option for continuous filling.



BIOCIDAL EFFICACY AND STEAM QUALITY

High-temperature, pressurised, disinfecting steam with permanent setting control.

TECHNICAL CHARACTERISTICS

Dimensions (L x W x H cm)	38.4 x 52 x 38 cm
Length (cm)	
- Steam hose	2 m
- Neoprene electrical cable	10 m
Empty weight	14 kg
Packaging	
- Dimensions (L x W x H cm)	70 x 55 x 46 cm
- Weight	18 kg
Boiler	
- Total volume	1.6 L
- Material / quality	Stainless steel 316 L
- Pressure	5.5 bar
- Boiler temperature	155°C
- Accessory outlet temperature	97°C
- Self-filling device	yes
- Steam flow rate	0 to 65 g/min
Electrical power	
- Power supply	230 V - 50 Hz
- Boiler	2400 W
- Total power input	2500W
- Immersion heater, dismantlable and anti-corrosion:	yes
Water tank capacity	2 L
Steam filter output	yes
Electrical protection class	IP 23
Disinfection effectiveness standard	NF T72-110
Machine standard	NF S98-120 (pending)

REFERENCE

DEVICE	REFERENCE
SP Mini KIT	SPMINIKIT

THE BIO-CLEANING PROCESS

1. PREPARATION

Preparation of the SP MINI Kit and controls (water level, cleanliness of accessories, connections, purging, etc.).

2. STEAM ACTION

The steam acts as a surfactant and suspends any dirt on the surface. The steam parameters are continuously monitored by the device to ensure its efficiency.

3. MECHANICAL ACTION

As the microfibre moves, it picks up dirt.

4. HEAT ACTION

The high temperature destroys bacteria and other germs.

5. DRYING PHASE

Any residual heat is released and the substrate is immediately dried, reducing the risk and therefore preventing the development of germs.



PRECAUTIONS FOR USE

Read all product information before use. Instructions for use are available on request by email: info@sanivap.fr

CONTENTS OF THE SP MINI KIT



SPMINI
Steam generator

Our 2500W steam generator.



SP200
Angled nozzle

For narrow and hard-to-reach areas.



SP240
Microfibre support

For small, high and flat surfaces.



SP252
Foldable MOP broom

For floors, walls and ceilings.



MV345 (10/sachet)

Double-layered microfibre cap for disinfecting small, high and flat surfaces.



MV450 (10/sachet)

Velcro microfibre for disinfecting wide and flat surfaces.



SN1320
Drainage key

Facilitates emptying the appliance (to be carried out every 20 hours of heating).



SP34
Seal kit

For maintenance of the appliance seals (to be carried out once a year).